SCHUTE HIGH RISE BOOD ROCK PICKER







- Shown with CE Shielding Kit -

8' Dump Height With Super Large 3cubic Yard Hopper Spend More Time Picking Less Time Running to the

Dump Site

- 1 Load trucks with ease!
- **2** Build larger stone piles!
- 3 Durable tapered T-iron grate with 1-1/2" (38mm) thick teeth eliminates jamming while allowing soil to sift through for clean rock picking.
- Batt tubing has 3/8" thick walls with wrap around, hard surfaced batt teeth for greater strength and wear resistance.
- 5 Large, heavy wire springs hold batts firmly in position and cushion shock loads. Spring coil diameter is reduced at the ends to minimize the possibility of breaking the spring hooks.
- **6** Floating grate protects the machine from damage due to large immovable rocks.
- Optional hydraulic pivoting hitch pole allows the machine to be quickly moved from the offset picking position to a centered transport position.
- S Large 16.5L X 16.1 10 ply tires provide superior flotation.



- Optional Dump Truck Bumper Kit -



- Optional Hydraulic Swing Kit -

SPECIFICATIONS

Weight Overall Length Overall Width with Tires Overall Width without Tires Hopper Capacity Picking Width Dumping Height Tire Size Minimum Tractor Size Tractor Hydraulic Requirements

Hydraulic Motor Displacement Final Drive Ratio Drive sprockets Crossover relief valve Recommended Reel Speed Pick rocks 6458lbs (2929Kg) 229" (5816mm) 115" (2921mm) 91" (2311mm) 3 cu. yards (2.29M³) 60" (1524mm) 96" (2438mm) 16.5L x 16.1 x 10ply(stand.) 85 hp (63Kw) 12 GPM @ 2200 psi, dual remote outlets 14.9 cu. inch/rev (244ml) 4:1 IIT and 45T #80 1750 psi cracking pressure 36 rpm 2" - 27" (5cm - 69cm)

HIGH RISE 8000

OPTIONS

Hydraulic Motor Valve Kit - this kit is used to meter oil between the hydraulic cylinders and the hydraulic motor so that reel speed does not decrease excessively when raising and lowering the grate. This option is useful on tractor models which use an open center hydraulic system

Hydraulic Swing Hitch - this kit provides a hydraulic cylinder which allows you to move the hitch in and out of transport position from the comfort of your cab

Dump Truck Bumper Kit - this kit provides adjustable bumpers that attach to the rear of the rock picker for backing up to trucks

CE shielding Kit - provides extra shielding in the grate and reel areas to meet European shielding requirements





Schulte Industries Ltd.,

P.O. Box 70, Englefeld, Saskatchewan, Canada SOK 1N0 Tel: (306) 287-3715 Fax: (306) 287-3355 E-Mail: info@schulte.ca Visit our Web site at: www.schulte.ca ISO 9001:2000





Shown with CE Shielding Kit -

STANDARD FEATURES

Flow Control Kit - this kit has a 0 to 15 GPM flow control valve which helps to control the reel speed. This option is useful on tractor models where hydraulic flow is not adjustable.

16.5L x 16.1 10 ply rib imp tires

The Schulte High Rise 8000 is hydraulically driven using a rugged Char-Lynn 2000 series hydraulic motor in combination with a flow control valve for reel speed adjustment and a crossover relief valve to cushion shock loads.

Grated hopper bottom helps sift out as much dirt as possible.

Batt tubing has 3/8" thick walls that stand up in the toughest conditions.

Three batt reel with high trip clearance provides superior performance in large rocks.

Full one year warranty on materials and workmanship.

SRW1400 Windrower



" The perfect companions to the Schulte High Rise 8000 are the Schulte models SRW1400 and SRW 800 Windrowers. These units windrow scattered rock from 2"-25" diameter, into neat rows. This greatly reduces the time required to clear rock and debris from the field.

Schulte Industries Ltd. reserves the right to change the design, material and specifications of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment. Part No. 1000-199

Sold By: